





Shenzhen Feelworld Technology Co.,Ltd  
 TEL:86-755-29968811 FAX:86-755-29968822 M.P: +86-13265586527  
 Attn: Coco Ma E-mail: Coco@szfeelworld.cn Website: www.feelworld.com.cn/www.seetec.com.cn  
 Add: Room 526-528,Zone B, Huameijiu, Xihu Road, 82th Baoan District, Shenzhen China

Model Show F6 Plus		Specification		
  		<b>Description</b>	5.5" 4K HDMI In&Out Capacitive Touchscreen LCD On-Camera Monitor with 3D LUTs	
		<b>Model</b>	F6 Plus	
		<b>Display</b>	<b>Screen Size</b>	5.5" IPS
			<b>Touch Screen</b>	Capacitive Touchscreen
			<b>Display Colors</b>	16.7M (8 bit)
			<b>Resolution</b>	1920x1080 pixels
			<b>Pixel Density</b>	440 PPI
			<b>Color Gamut</b>	90% NTSC, Rec. 709 Color Calibration
			<b>Aspect Ratio</b>	16:9
			<b>Brightness</b>	500cd/m2
			<b>Contrast</b>	1000:1
			<b>Backlight</b>	LED
		<b>Adjustable Backlight</b>	YES	
		<b>Viewing Angle</b>	85°/85°(L/R) 85°/85°(U/D)	
		<b>Connectors</b>	<b>Input Signal</b>	HDMI v1.4
<b>Outputs</b>	HDMI, DC output			
<b>Audio</b>	3.5mm Stereo Out (headphone)			
<b>HDMI Input Support Format</b>	480i/576i/480p/576p			
	1080i (60/59.94/50)			
	720p (60/59.94/50/30/29.25/24/23.98)			
	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)			
	4K UHD 3840×2160p (30/29.97/25/24/23.98Hz), DCI 4K 4096×2160p (24Hz)			
	<b>SD Card Slot</b>	SD Card for LUT Loading, Firmware Upgrades		
<b>Power</b>	<b>Power Out</b>	DC 8V to power camera with a separately available DC coupler		
	<b>Power Consumption</b>	≤ 10W		
	<b>Input Voltage</b>	DC7 ~24V		
	<b>Battery Plate</b>	Dual-Purpose Battery Plate (NP-F and LP-E6)		
	<b>Power Connector</b>	DC (5.5mm outer, 2.1mm inner)		
<b>General</b>	<b>Operating Temperature</b>	-20℃ ~ 55℃		
	<b>Storage Temperature</b>	-30℃ ~ 65℃		
	<b>Mounting Points</b>	(3) ¼-20 thread points (top, bottom, & right side), Tilt Arm is included		
	<b>Unit Size</b>	148Lx93Hx21D (mm)		
	<b>Unit Weight</b>	235g		
<b>3D LUT</b>				
<b>3D LUT Log to Rec709</b>				
User LUT cube import				
F6 Plus provides more than 20 De-log 3DLUTs, Including S-log2/3, V-log, C-log1/2/3, Log-C, J-log1, RedLog, BMD, FujiFilm, GoPro, DJI etc, to convert log mode to REC709 for all major cameras.				
<b>User 3DLUT upload</b>				
User creative 3D LUT cube or calibration 3D LUT cube can be uploaded to F6 plus by SD card. Max to 16 user 3D LUTs can be restored.				
<b>Key Features</b>				
*Audio Meters		*Power out DC 8V to power camera with a separately available DC coupler		
*Histogram		*Image Flip (H, V, H/V)		
*Focus Assist (Red, Green, Blue three colors optional highlight over parts of the image in focus)		*Image Freeze		
*False Colors		*Color Temperature Adjustment		
*Zebra Exposure (1-100IRE adjustable)		*Nine Grid (Zoom one of the images to realize the full screen)(Nonsupport in 4K input)		
*Camera Mode(DSLR Scale)		*Zoom (with smooth pan via pinch zoom gesture)		
*Anamorphic de-squeeze (1.3X, 2.0X, 2.0X MAG)		*Zoom All		
*Center Marker		*Pixel to Pixel		
*Safe Frames (80%, 85%, 90%, 93%, 96%, 2.35:1)		*Aspect Ratio		
*Ratio Marker (4:3, 13:9, 14:9, 15:9, 16:9, 1.85:1, 2.35:1)		*Scan Mode (Under Scan, Over Scan)		
*Marker Color (Red, Green, Blue, White, Black)		*Marker Mat		
*Check Field (Red, Green, Blue, Mono)		*Swivel monitor via Tilt Arm design		
<b>Standard Accessory</b>		<b>Packing Details</b>		
HDMI to Micro HDMI Cable	DC12V Power Adapter	<b>Box Size</b>	18.6*12.5*10.2cm	
Tilt Arm	F970 Battery/F770 Battery/F550 Battery +charger	<b>Per box G.W.</b>	1kg	
Sunshade	Sony FW50 Dummy battery	<b>Per Carton</b>	10pcs	
Sunshade mounting frame	Panasonic DMW-BLF19 Dummy battery	<b>Carton Size</b>	58*20*32cm	
Manual	Canon LP-E6 Dummy battery	<b>G.W.</b>	8kg	
	Sony Dummy battery FZ100 for A7M III			

